Clean version of amended claims

1.   A method of displaying information by a network kiosk comprising the steps of:

sensing a person within a predetermined distance of the kiosk;

displaying first information in response to said sensing step;

timing a time period of displaying the first information; and

displaying second information if the person does not begin use of the kiosk within the time period.

2.   A method of displaying information by a network kiosk comprising the steps of:

sensing a person within a predetermined distance of the kiosk;

displaying first information in response to said sensing step;

timing a time period of displaying the first information; and

displaying second information if the person is no longer within the predetermined distance of the kiosk and the time period has expired.

2

3.   A method of displaying information by a network

kiosk comprising the steps of:

displaying first information;

sensing a person within a predetermined distance of the

kiosk;

displaying second information in response to said

sensing step;

timing a time period of displaying the second

information; and

displaying third information if the person is no longer

within the predetermined distance of the kiosk and the time

period has expired.

4.   A method of displaying information by a network

kiosk comprising the steps of:

displaying first information;

sensing a person within a predetermined distance of the

kiosk;

determining second information for display in response

to said sensing step;

displaying the second information;

timing a time period of displaying the second

information to wait for the person to operate the kiosk;

3

determining third information for display when the

person is no longer within the predetermined distance of the

kiosk and the time period has expired; and

displaying the third information.

5.   A network kiosk comprising:

a display for displaying information;

a proximity sensor; and

a computer which senses a person within a predetermined

distance of the kiosk, displays first information in

response to sensing the person, times a time period of

displaying the first information, and displays second

information if the person does not begin use of the kiosk

within the time period.

6.   A network kiosk comprising:

a display for displaying information;

a proximity sensor; and

a computer which senses a person within a predetermined

distance of the kiosk, displays first information in

response to sensing the person, times a time period of

displaying the first information, and displays second

information if the person is no longer within the

predetermined distance of the kiosk and the time period has

expired.

4